

Miller ProHeat 35

Unit Serial Number: MC090109G Date Tested: 11/21/2013

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VCD@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.787	383	6.013	882	9.238	1382
TC2	2.790	383	6.028	883	9.247	1383
TC3	2.791	383	6.019	882	9.240	1382
TC4	2.792	383	6.018	883	9.240	1382
TC5	2.793	383	6.010	883	9.239	1382
TC6	2.787	383	6.012	883	9.237	1383
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1882015 Calibration Date: 12/17/2012

Precision Digital Voltage Meter SN: 2036021 Calibration Date: 12/17/2012

Machine re-calibration due date: 11/21/2014

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: Sal H. Date: 11/21/2013

Signature