

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: MC450062G

Date Tested: 23/08/13

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.793	383	6.022	882	9.250	1382
TC2	2.789	383	6.019	883	9.246	1382
TC3	2.796	383	6.021	883	9.248	1383
TC4	2.797	384	6.028	884	9.252	1383
TC5	2.796	384	6.020	884	9.251	1384
TC6	2.799	384	6.033	884	9.258	1384
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2118055

Calibration Date: 09/08/13

Precision Digital Voltage Meter SN: 2142011

Calibration Date: 09/08/13

Machine re-calibration due date: 23/08/14

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician:

Guro Rodin Date: 23/08/13

Signature

Montreal Canada office