



## Calibration Certificate

### Miller ProHeat 35

Unit Serial Number: ME040113G

Date Tested: 19-JUN-17

#### Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VCD@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.784	382	6.011	882	9.239	1381
TC2	2.781	382	6.013	882	9.247	1382
TC3	2.788	383	6.016	882	9.247	1382
TC4	2.792	383	6.025	883	9.243	1383
TC5	2.798	383	6.024	883	9.248	1383
TC6	2.794	383	6.012	883	9.244	1382
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

#### Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2097001

Calibration Date: 13-MAR-17

Precision Digital Voltage Meter SN: 2142012

Calibration Date: 13-MAR-17

Machine re-calibration due date: 19-JUN-18

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician:

Date: 19JUN17

Signature